

PRO-S SPRINKLER



Product Features


Co-molded wiper seal

Ensures a leak free, full pop-up operation even under low-pressure situations. Cartridge design allows for easy removal and cleaning. Treated with UV inhibitors for long life. Seal is microbe resistant to reduce degradation and stick-ups.



Ratcheting riser

Permits quick and easy alignment of spray pattern.



Heavy duty retraction spring

Strongest spring in the industry for positive retraction in all soil conditions.



Side inlet

Standard on 12" model. 6" model available with or without side inlet.

Optional in-stem check valve

Installs in the field and holds up to 3m of head pressure

Pre-installed flush cap

Accepts female threaded nozzles

Optional pre-installed nozzle guard

Suitable for Residential and Light Commercial Application

Inlet: 1/2" (15mm) female threaded NPT

Flow by: 0.8L/min

Pressure Rating: 20-70 PSI (140-490kPa)

Overall Body Height:

78002	4"	(100mm)
78003	4 7/8"	(125mm)
78004	6"	(150mm)
78006	9 3/8"	(240mm)
78012	16"	(406mm)

Order Details

SK78002
SK78003
SK78004
SK78006
SK78012

WWW.K-RAIN.COM.AU



IMPORTED FROM
K-RAIN USA

K
RAIN®

**Landscaper's
Choice**